

■ 3 Phase Starters

Section 2

DOL 3 Phase Starters – Plastic Enclosed

Maximum 3 Phase Motor rating as 415V KW HP		Maximum Motor Current AC3 Amps	Overload Type	Part Reference	Price Each
4.5	5.5	9	RF25	DOL4V5WO*	35.39
7.5	10	16	RF25	DOL7V5WO*	49.55
11	15	25	RF 25	DOL11WO*	70.78

Start Stop Pushbuttons

Plastic Enclosure
IP54 (4.5 & 7.5 KW)
IP65 (11KW)

Overload to be ordered separately



DOL 3 Phase Starters – Plastic Enclosed

Maximum 3 Phase Motor Rating at 415V KW HP		Maximum Motor Current AC3 Amps	Overload Type	Part Reference	Price Each
4.5	5.5	8	RF25	LVMDOL4V5WO*	92.03
7.5	10	10	Rf25	LVMDOL7V5WO*	96.73

Start Stop Pushbuttons

Steel Enclosure IP66

Optional lockable three-phase Isolator



Plastic Enclosed



Steel Enclosed

DOL 3 Phase Isolated Starters – Steel Enclosed

Maximum 3 Phase Motor Rating at 415V KW HP		Maximum Motor Current AC3 Amps	Overload Type	Part Reference	Price Each
4.5	5.5	9	RF25	LVMDOL14V5WO*	139.20
7.5	10	16	RF25	LVMDOL17V5WO*	143.92

DOL Single Phase Starters – Plastic Enclosed

Maximum Single Phase Motor rating at 240V		Maximum Motor Current AC3 Amps	Overload Type	Part Reference	Price Each
KW	HP				
1.1	1.5	10	RF25	SPD1V1WO*	41.28
1.8	2.5	23	RF25	SPD1V8WO*	49.55
3.7	5	33	RF25/RF95	SPD3V7WO*	94.37



Overload Selection – 3 Phase DOL's

Overload Range Amps	Part Reference Overload	Price Each	Part Reference DOL 3 Phase Starter
0.09-0.15	RF25.015	21.83	DOL4V5WO LVMDOL(I)4V5WO DOL7V5WO LVMDOL(I)7V5WO DOL11WO
0.14-0.23	RF25.023	21.83	
0.2-0.33	RF25.033	21.83	
0.3-0.5	RF25.05	21.83	
0.45-0.75	RF25.075	21.83	
0.6-1	RF25.1	21.83	
0.9-1.5	RF25.1V5	21.83	
1.4-2.3	RF25.2V3	21.83	
2-3.3	RF25.33	21.83	
3-5	RF25.5	21.83	
4.5-7.5	RF25.75	21.83	
6-10	RF25.10	21.83	
9-15	RF25.15	21.83	
14-23	RF25.23	25.96	
17-26	RF25.26	32.01	

Overload Selection – Single Phase DOL's

Overload Range Amps	Part Reference Overload	Price Each	Part Reference DOL Single Phase Starter
0.09-0.15	RF25.015	21.83	SPD1V1WO SPD1V8WO SPD3V7WO
0.14-0.23	RF25.023	21.83	
0.2-0.33	RF25.033	21.83	
0.3-0.5	RF25.05	21.83	
0.45-0.75	RF25.075	21.83	
0.6-1	RF25.1	21.83	
0.9-1.5	RF25.1V5	21.83	
1.4-2.3	RF25.2V3	20.95	
2-3.3	RF25.33	21.83	
3-5	RF25.5	21.83	
4.5-7.5	RF25.75	21.83	
6-10	RF25.10	21.83	
9-15	RF25.15	21.83	
14-23	RF25.23	25.96	
17-26	RF25.26	32.01	
20-33	RF95 0 33	48.83	

DOL 3 Phase Reversing Starter – Plastic Enclosed

Maximum 3 Phase Motor Rating at 415V KW HP	Maximum Motor Current AC3 Amps	Overload Type	Part Reference	Price Each
4 5.5	9	RF9	DOLR4WO*	117.96

Overload to be ordered separately

Forward, Stop, Reverse Pushbuttons

IP55 Plastic Enclosure

Mechanically and electrically interlocked contactors

